

FRONT

EarthWorks™

Growth products for professional turf management

Kick 0-1-2

Soil Conditioner and Liquid Nutrient

Develops strong root system
Humic acid

23Lbs (10.4Kg)
(2.5 gallons / 9.5 liters)

BACK

**Kick 0-1-2
Soil Conditioner & Liquid Nutrient**

Use Instructions

Turf Maintenance

Apply 6 to 8 ounces per 1000 sq. ft. in 2 gallons of water every two weeks throughout the growing season— preferably in split applications. Kick may be mixed with most fertilizers and pesticides, enhancing the effectiveness of these materials and allowing for a reduction in their rates.

New Seeding

Apply 6 ounces per 1000 sq. ft. in a minimum of 2 gallons of water at time of seeding and again 4 to 6 weeks later. May be used with starter fertilizers.

Sod Installations:

After laying sod, thoroughly soak with a dilution of 6 ounces per 1000 sq. ft. in at least 2 gallons of water. Repeat every 6 weeks for first year or two.

Compacted Soils

Use 8 ounces per 1000 sq. ft. in 5 gallons of water. Repeat application in one week. In times of heavy play, repeat this application process every 60 days.

Tree Soil Injection

Add 1 quart per 100 gallons to cover 3000 sq. ft. of root area and apply every 60 days. For stressed and damaged trees, reduce coverage to 1500 sq. ft. root area.

Landscaping Maintenance

Drench soil with 4 ounces in 2 gallons of water every 60 days.

Avoid Mixing with excessive phosphorus or sulfur containing materials. Always perform a bench test for compatibility.

Guaranteed Analysis

Available Phosphate (P₂O₅) 1.00%
Soluble Potash (K₂O) 2.00%

Derived from: Molasses, Kelp Extract and Phosphoric Acid

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS:

Guaranteed Analysis

10% Organic matter (Derived from Molasses and Kelp)
4.0% Ammonium Lauryl Sulfate (Surfactant)
4.0% Oilseed Extract (Surfactant)
1% Humic Acid (Derived from Leonardite)

81% - Other Ingredients

Organic matter in the Molasses and Kelp Extract is a source of carbon that serves as food for soil microbes. Humic acids may aid in micronutrient uptake. Surfactants are used to reduce the surface tension of liquids allowing easier penetration into soil.

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

Condition of Sale

1. Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. No one, other than an officer of Seller, is authorized to make warranty, guarantee or direction concerning this product.
2. Because the time, place, rate of application and other conditions of use are beyond Seller's control, Seller's liability from handling, storage and use of this product is limited to replacement of product or refund of purchase price.

Storage Precautions

Store in manufacturer's containers when possible. If not, store in polyolefin or polyethylene storage tanks. Do not store for extended periods in mild steel and only in approved fiberglass. Although stainless steel tanks are less prone to corrosion than mild steel, they are not recommended for extended storage. Do not use nylon fittings and valves. PVC or polypropylene valves and fittings are recommended.

CAUTION: KEEP OUT OF REACH OF CHILDREN WARNING

Harmful if swallowed. Avoid breathing spray mist. May cause irritation of nose, throat, and/or skin. Avoid contact with the eyes, skin and clothing. If swallowed: induce vomiting by sticking finger down throat. Never give anything by mouth to unconscious person. Get medical attention immediately. If in eyes, wash eyes with plenty of clear water for at least 15 minutes. Get medical attention immediately.

Keep stored above 32°F or 0°C
DO NOT ALLOW TO FREEZE

Guaranteed by:

EarthWorks
1500 Uhler Road
Easton, PA 18040
800 732-TURF
www.earthworksfirst.com

F1399